

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)


PCT

(10) International Publication Number
WO 2004/014255 A1

- (51) International Patent Classification⁷: **A61F 2/06** (74) Agent: **VOSSIUS & PARTNER**; Siebertstrasse 4, 81675 Munich (DE).
- (21) International Application Number: **PCT/EP2003/008384** (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: **29 July 2003 (29.07.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data: **60/402,136** **7 August 2002 (07.08.2002)** **US** (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): **ABBOTT LABORATORIES VASCULAR ENTERPRISES, LIMITED [IE/IE]**; Earlsfort Center, Terrace, Dublin 2 (IE).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): **CALISSE, Jorge [DE/DE]**; Kirchensrasse 4, 14199 Berlin (DE). **BESSELINK, Petrus, A. [NL/NL]**; Gronausestraat 1220, NL-7534 AT Enschede (NL). **Published:**
— *with international search report*

[Continued on next page]

(54) Title: **APPARATUS FOR A STENT OR OTHER MEDICAL DEVICE HAVING A BISTABLE SPRING CONSTRUCTION**



(57) Abstract: A stent is described comprising a unit cell having a negative spring rate and a bistable function. The unit cell comprises first and second segments, the first segment being more rigid than the second segment. The second segment is coupled to the first segment, and the first segment comprises a substantially fixed sinusoidal shape. In the contracted state, the second segment is held stable in a sinusoidal shape, but when a force is applied the second segment bends out to a stable, convex-shaped deployed state. The second segments withstand the application of radial forces in the convex-shaped deployed state, and diametral recoil of the stent is minimized.

WO 2004/014255 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.